



CANT STRIP & TAPERED EDGE

ROOF TRANSITION COMPONENTS

DESCRIPTION

CANT STRIP and **TAPERED EDGE** are widely accepted, high quality low slope roofing products. Each is durable, lightweight and environmentally friendly.

USES

CANT STRIP offers excellent transition and sloping properties and compatibility with most conventional roof systems. (See membrane manufacturer for approval.) **TAPERED EDGE** is manufactured to enhance roof drainage and reduce ponding water.

FEATURES/BENEFITS

- More durable than perlite
- High R-value
- Dimensionally stable
- Environmentally friendly, 100% recyclable wood fiber
- May contribute to LEED credits
- Cuts with a knife; lightweight; contractor preferred

MEASUREMENTS

CANT STRIP

Product Name	Specific Measurements	Shape
1" x 3"	1" T x 2-3/4" F x 48" L	
1" x 4"	1" T x 3-3/4" F x 48" L	
1-1/2" x 4"	1-1/2" T x 3-5/8" F x 48" L	
1-1/2" x 5"	1-1/2" T x 5" F x 48" L	

TAPERED EDGE STRIP

Product Name	Specific Measurements	Shape
1/2" X 6"	1/2" to 0" T x 6" W x 48" L	
1/2" X 12"	1/2" to 0" T x 12" W x 48" L	
1" X 8"	1" to 0" T x 8" W x 48" L	
1" X 12"	1" to 0" T x 12" W x 48" L	
1" X 24"	1" to 0" T x 24" W x 48" L	
1-1/2" X 12"	1-1/2" to 0" T x 12" W x 48" L	
1-1/2" X 18"	1-1/2" to 0" T x 18" W x 48" L	
1-1/2" X 24"	1-1/2" to 0" T x 24" W x 48" L	
2" X 24"	2" to 0" T x 24" W x 48" L	

SPECIFICATIONS

- Conforms to ASTM C 208, Type II - Roof insulation board

TECHNICAL DATA

Physical Property	Typical Value	Test Method
Water Absorption	≤10%	ASTM C 209
Transverse Strength @ 1.5"	24 lbf	ASTM C 209
Tensile Strength (Perpendicular)	500 lbf/ft. ²	ASTM C 209
Density	14-16 pcf	ASTM D 1037
R-Value @ 1.5" Thickness	3.5 h-ft. ² -°F/Btu	ASTM C 518

APPLICATION

CANT STRIP ... Install for a sloping transition of horizontal to vertical surfaces.

TAPERED EDGE ... Elevate and slope roof for positive drainage. TAPERED EDGE can be installed on wood, metal, or concrete decks. TAPERED EDGE improves roof drainage, eliminating ponding water, and can be used on both new and re-roof projects.

LEED INFORMATION

May help contribute to:

MR Credit: Recycled Content

MR Credit: Regional Materials

MR Credit: Rapidly Renewable Materials

IEQ Credit: Low-Emitting Materials - Composite Wood and Agrifiber Products

Limited Warranty: BLUE RIDGE FIBERBOARD, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

Disclaimer: The information contained herein is included for illustrative purpose only, and to the best of our knowledge, is accurate and reliable. BLUE RIDE FIBERBOARD, INC. cannot however under any circumstance make any guarantee of results or assume any obligation or liability in connection with the use of this information. As BLUE RIDGE FIBERBOARD, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.

© 2018 BLUE RIDGE FIBERBOARD, INC.